



## OneFlow® + Whole Home Scale Prevention & Water Filtration

Efficient, economical, and environmentally friendly – the OneFlow®+ protects pipes, extends appliance lifespan, and provides great tasting, filtered water!

- **Rated most effective scale prevention technology†**
- **Offers homeowners up to £240 of savings annually‡**
- **Environmentally friendly – salt-free, chemical-free, no electricity, no wastewater**
- **Incredible tasting water at every tap – reduces chlorine taste and odour**
- **Virtually maintenance-free§**
- **High capacity**
- **Easy installation**

†WaterReuse Research Foundation, Evaluation of Alternatives to Domestic Ion Exchange Water Softeners, 2013

‡Based on 4-person home using 75 gallons per person daily §Annual / Triennial filter replacement

### OneFlow® Media Technology

Using our OneFlow® Media technology, the OneFlow®+ Scale Prevention Catridge attracts and converts “hard” minerals in your customer’s water supply into harmless, inactive “soft” scale particles. These particles stay suspended in water and flow freely through a system instead of building up inside pipes. OneFlow Media technology does not add or remove anything from water, allowing useful minerals such as calcium, potassium, and magnesium to remain.



Contact your local Watts representative today to order!  
**Call 01352 838281 (Fountain Filters)**

# Ordering Information

## OneFlow®+ Whole Home Scale Prevention & Water Filtration

| MODEL NO. | ORDERING CODE | DESCRIPTION                                             |
|-----------|---------------|---------------------------------------------------------|
| OFPSYS    | 7100638       | OneFlow+ Whole Home Scale Prevention & Water Filtration |
| OFPRFC    | 7100639       | Radial Flow Carbon Block Cartridge                      |
| OFPSP     | 7100640       | OneFlow Cartridge                                       |
| OFPCOM    | 7100641       | Combo Pack Includes Carbon Block and OneFlow Cartridge  |

| Operating Conditions   |                                                                                        |
|------------------------|----------------------------------------------------------------------------------------|
| Rated Flow             | Max 10 gpm                                                                             |
| Working Temp           | 40 - 100° F (4.4 - 38° C)                                                              |
| Working Pressure       | 10 - 90 psi - a pressure limiting valve must be installed when pressure exceeds 70 psi |
| Working Conditions     | For indoor use - protection required when installed outdoors                           |
| Size                   | 10-in x 10-in x 18-in                                                                  |
| Min Net Weight         | 15 lbs                                                                                 |
| Contaminants Reduced   | Scale, sediment, other chemicals, chlorine taste and odor                              |
| Conditions For Use     |                                                                                        |
| pH                     | 6.5-8.5                                                                                |
| Hardness (maximum)     | 30 grains (513 ppm CaCO <sub>3</sub> )                                                 |
| Water Pressure         | 10 psi to 90 psi (0.69 bar to 6.2 bar)                                                 |
| Temperature            | 40° F to 100° F (5°C to 38°C)                                                          |
| Free Chlorine          | <2 ppm                                                                                 |
| Iron (maximum)         | 0.3 ppm                                                                                |
| Manganese (maximum)    | 0.05 ppm                                                                               |
| Copper                 | 1.3 ppm                                                                                |
| Oil & H <sub>2</sub> S | Must be Removed Prior to OneFlow                                                       |
| Total Polyphosphates   | < 3.0 ppm                                                                              |
| Silica (maximum)       | 20 ppm                                                                                 |
| TDS                    | 1500 mg/l                                                                              |

Get Started Today



**USA:** T: (800) 224-1299 • F: (978) 794-1848 • [Watts.com/PureWater](https://Watts.com/PureWater)  
**Canada:** T: (905) 332-4090 • F: (905) 332-7068 • [Watts.ca/PureWater](https://Watts.ca/PureWater)  
**United Kingdom:** T: +44 (0) 1480 407074 • [Wattswater.co.uk/catalog/water-quality/](https://Wattswater.co.uk/catalog/water-quality/)